

RUBBER WHEEL STOPS – 1650MM

Reflective rubber wheel stops for car park bays. A low-cost way to mark bays and stop vehicles overrunning a kerb or wall.

SW-WS1650

SPECIFICATION	WHEEL STOP 1650MM
SKU	SW-WS1650
Length	1650mm
Width	150mm
Height	100mm
Weight	approx. 12kg
Material	Moulded rubber, reflective yellow markings
Fixing	Moulded holes for concrete anchors or asphalt spikes
Indicative price	from \$50 / unit
Availability	Pre-order, next shipment

FINISH & CONSTRUCTION

- Moulded rubber: weather resistant, won't rust or corrode
- Reflective yellow markings for low-light visibility
- Fixing holes moulded in for concrete or asphalt anchoring
- Length suits a standard passenger vehicle bay

WHAT'S INCLUDED

- Wheel stop
- Anchors and spikes not included

INSTALLATION (SUMMARY)

- Concrete: fix through the moulded holes with M10 or M12 concrete anchors
- Asphalt or gravel: use 300mm asphalt spikes or screw anchors instead
- Set back from walls and kerbs to allow for vehicle overhang; follow AS 2890.1 and the site drawings for bay layout
- Keep the row square and consistent with a chalk line

Safety and delineation product: not impact-tested or certified to hostile-vehicle standards (PAS 68 / IWA 14). Dimensions are nominal, taken from manufacturing drawings. SafeWise supplies product only; installation is the responsibility of the purchaser or their contractor. Locate underground services before drilling or excavating.